


SPECIFICATION ALL-STAR™ PANELS

PROJECT	DATE
TYPE	QTY




ACOUSTIC FABRIC STAR CEILING PANELS



STAR PANEL 2'x2': Acoustical Substrate
W-2' x W-2' x H-3/4"

STAR PANEL 2'x2': Acoustical Fabric Wrapped Panel
W-2' x W-2' x H-1"



STAR PANEL 2'x2': Acoustical Substrate
W-2' x W-4' x H-3/4"

STAR PANEL 2'x2': Acoustical Fabric Wrapped Panel
W-2' x W-4' x H-1"

KEY FEATURES:

- 2.4W per panel / 12V (low voltage)
- UL fire rated materials.
- Materials: Fabric wrapped acoustical panel or acoustical cast mineral fiber panels
- Realistic Star effects.
- 5 Year Limited Warranty

Made specifically for for drop-in ceiling tile grids, epiXsky's ALL-STAR™ PANEL is a modular star panel system that easily transforms existing ceiling tiles to a captivating starfield.

The system includes our twilight white proprietary LED light source that creates our famous white stars featuring 3-D effects.

Epix ALL-STAR™ PANEL SYSTEMS operate in standalone mode with off/on only.

ALL-STAR™ PANELS COME IN 2 OPTIONS:

1) ALL-STAR™ STANDARD: Acoustic Ceiling Tiles.

1/2 inch thick, 2'x2' and 2'x4', pre-wired with end glow fiber optics. Ready to insert in any existing ceiling grid system.

Black Only

1) ALL STAR™ PRO: Acoustical Fiberglass Panels Wrapped in Acoustical Fabric.

1 inch thick, 2'x2' and 2'x4' pre-wired with end glow fiber optics. Ready to insert in any existing ceiling grid system.

The Acoustic fiberglass and acoustical fabric and extra thickness give the PRO VERSION slightly more acoustic properties than the standard ALL-STAR.

Fabrics come in different colors. Custom colors are additional cost and timeframe.

CUSTOM COLORS AVAILABLE
The most dense star field on the market.

ORDERING

MODEL	SIZE	FABRIC COLOR	SIZE	COMMUNICATION/POWER	STAND ALONE SPECIAL EFFECTS
AS - ALL-STAR™ Black Fissured Ceiling Tile (2x2 only)	2 x 2 2 x 4	BLK - Black (Std.) WH - White EG - Eggshell MG - Medium Grey	2 x 2 2 x 4	EL - Epic Link <i>(required for both ALL-Star™ products; Over 100 panels will require another link)</i>	SS - Shooting Star (2,5,10min intervals) FWW - White Firework (constant run) FWC - Color Firework (constant run) CN - Constellation GXW - Galaxy (white, slight twinkle) GXC - Galaxy (purple & blue, slight twinkle) 3DMN - 3D Moon w/ Accent Lighting AE - 3D Earth w/ Accent Lighting AM - 3DMars w/ Accent Lighting
ASP - ALL-STAR™ PRO Fabric Wrapped Acoustical Panel (color options)		BP - Blue Plum BB - Bayberry CU - Custom* <i>(Specify Custom Color from page 2)</i> <i>* Additional Cost</i>			

(to control special effects through an APP or third party controller requires separate components please call for more information)



A Division on Impact Lighting Inc.

3080 Lenworth Dr. • Mississauga, ON • L4X 2G1 • Email: sales@epiXsky.com



V. 521 | Copyright © 2021, Impact Lighting Inc. All Rights Reserved

SPECIFICATION ACOUSTIC PANELS

PROJECT	DATE
TYPE	QTY



FABRIC COLORS FOR ACOUSTIC STAR CEILING PANELS

LIME	CHARTREUSE	CARDINAL	SKY
TEAL	FIR	YELLOW	SAPPHIRE
ORANGE	BLUE PAPIER	WHEAT	* EGGSHELL
WEDGEWOOD	BALTIC	CRYSTAL BLUE	* WHITE
GREY MIX	* MEDIUM GREY	QUARTZ	AQUAMARINE
OPAL	CHERRY NEUTRAL	BLUE NEUTRAL	GREEN NEUTRAL
VANILLA NEUTRAL	APRICOT NEUTRAL	LAVENDAR NEUTRAL	SILVER NEUTRAL
* BLACK	CLARET ACCENT	COBALT	CINNABAR
PUMICE	BUFF	BLUE SPRUCE	EUCALYPTUS
ULTRAMARINE	STEEL GREY	PEARL	* BAYBERRY
SILVER PAPIER	* BLUE PLUM	DEEP BURGUNDY	VERTE PAPIER
STRAW	BONE	DUNE	CEMENT MIX
TERRA	LIGHT MOSS	LEAF	STREAM
DESERT SAND	EARTH	CHOCOLATE	COIN
FLANNEL	MOLESKIN	SUNSHINE	IRIS
	RED	AMETHYST	

(* Standard Colors)

SPECIFICATIONS:

CONTENT:
100% post-consumer recycled polyester

WEIGHT:
16.0 ± 0.5 oz./lin. yd.

WIDTH:
66" min. useable

REPEAT:
none

BACKING:
none

TREATMENT:
none

CLEANING CODE:
Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

PERFORMANCE:

BREAKING STRENGTH (ASTM D5034)
150 lbf min. warp and fill

COLORFASTNESS TO LIGHT (AATCC 16.3 OPTION 3)
Grade 4 min. at 40 hours

COLORFASTNESS TO CROCKING (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

FLAMMABILITY
ASTM E84 Class I or A.



Terratex is a registered trademark of Duvaltex and designates fabrics that are made from 100% recycled or compostable material using increasingly sustainable manufacturing practices to produce a high quality product that is recyclable at the end of its useful life.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

ORDERING

MODEL	—	COLOR
APF		
Acoustic Panel Fabric		Choose From Above



A Division on Impact Lighting Inc.

3080 Lenworth Dr. • Mississauga, ON • L4X 2G1 • Email: sales@epiXsky.com

epiXsky.ca